

# weavix Earpiece Specifications



## Stay Connected

Our over-the-ear headset keeps you in the loop with crystal-clear communication. Whether you're coordinating with your team or collaborating on a project, this headset ensures seamless connectivity.

## Push-to-Talk Convenience

Need to relay important information? Just press the button! The attached microphone lets you communicate effortlessly, without missing a beat.

## Tangle-Free Design

Say goodbye to messy wires! Our headset features a secure, attached wire that won't get lost. No more fumbling around.



## Specifications

### Rated Impedance

**32Ω ± 15%**

At 1.3K Hz, 1.0 Vrms

### Frequency Range

**400 ~ 8KHz**

By Output S.P.L. -10dB

### Rated Input Power

**0.5 Watt**

At 4.0Vrms white noise 96Hours

### Diaphragm over buffer

**0mm**

Sinewave 4.0V ,at 50~ 5000Hz

### Resonant Frequency

**650 ± 100Hz**

With the following measurement conditions.

### Distortion

**Less than 5%**

At 1.4KHz, 4.0Vrms ,Sweep Speed: 1/3Oct

### Output S.P.L

**95 ± 3dB**

(0.5 Watt 0.1 Meter)

Average at 1.0K, 1.2K, 1.5K, 2.0KHz; 4.0Vrms acc. to IEC-60268

### Operating Temperature

**-25°C ~ +50°C**

With the following measurement conditions.

### Max. Input Power

**1.0 Watt**

Must be normal at a white noise (1.0W) for 1 min at max power, Stop 2 minutes for the cycle test for 10 circle

### Storage Temperature

**-25°C ~ +55°C**

With the following measurement conditions.

